

Tabella Prestazioni testine statiche regolabili

8A				10A				12A				15A				17A			
ARC.	bar	m	l/min	ARC.	bar	m	l/min	ARC.	bar	m	l/min	ARC.	bar	m	l/min	ARC.	bar	m	l/min
90°	1.00	1.70	0.75	90°	1.00	2.10	0.63	90°	1.00	2.70	1.62	90°	1.00	3.40	2.39	90°	1.00	4.70	3.08
	1.50	2.10	0.93		1.50	2.40	0.79		1.50	3.20	2.02		1.50	3.90	2.89		1.50	4.90	3.85
	2.10	2.70	1.12		2.10	3.30	0.95		2.10	4.00	2.43		2.10	4.90	3.59		2.10	5.50	4.63
	2.50	2.80	1.24		2.50	3.50	0.95		2.50	4.20	2.68		2.50	5.20	3.95		2.50	5.70	5.10
180°	1.00	1.70	1.49	180°	1.00	2.10	2.52	180°	1.00	2.70	3.23	180°	1.00	3.40	4.77	180°	1.00	4.70	6.16
	1.50	2.10	1.87		1.50	2.40	3.14		1.50	3.20	4.04		1.50	3.90	5.97		1.50	4.90	7.70
	2.10	2.70	2.25		2.10	3.30	3.78		2.10	4.00	4.86		2.10	4.90	7.18		2.10	5.50	9.27
	2.50	2.80	2.47		2.50	3.50	4.16		2.50	4.20	5.35		2.50	5.20	7.90		2.50	5.70	10.20
270°	1.00	1.70	2.24	270°	1.00	2.10	3.77	270°	1.00	2.70	4.85	270°	1.00	3.40	7.16	270°	1.00	4.70	9.24
	1.50	2.10	2.80		1.50	2.40	4.72		1.50	3.20	6.06		1.50	3.90	10.49		1.50	4.90	11.55
	2.10	2.70	3.37		2.10	3.30	5.68		2.10	4.00	7.30		2.10	4.90	10.77		2.10	5.50	13.90
	2.50	2.80	3.71		2.50	3.50	6.25		2.50	4.20	8.03		2.50	5.20	11.86		3.45	5.70	13.90
360°	1.00	1.70	2.99	360°	1.00	2.10	5.03	360°	1.00	2.70	6.47	360°	1.00	3.40	9.55	360°	1.00	4.70	9.24
	1.50	2.10	3.73		1.50	2.40	6.29		1.50	3.20	8.09		1.50	3.90	11.94		1.50	4.90	11.55
	2.10	2.70	4.49		2.10	3.30	7.57		2.10	4.00	9.73		2.10	4.90	14.36		2.10	5.50	13.90
	2.50	2.80	4.94		2.50	3.50	8.33		2.50	4.20	10.71		2.50	5.20	15.81		2.50	5.70	20.40